

UK DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (BS EN 13501-5, BS DD CEN/TS 1187)

Reaction to fire (BS EN 13501-1, BS EN ISO 11925-2)

Watertightness (BS EN 1928/B)

Tensile strength (BS EN 12311-2/A)

Elongation (BS EN 12311-2/A)

Resistance to root penetration (BS EN 13948)

Resistance to static load (BS EN 12730/B and C)

Resistance to impact (BS EN 12691/A)

Resistance to impact (BS EN 12691/B)

Tear resistance (BS EN 12310-2)

Joint peel resistance (BS EN 12316-2)

Joint shear resistance (BS EN 12317-2)

Artificial ageing (BS EN 1297)

Foldability at low temperature (BS EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

Signed for and on behalf of the manufacturer by:

Sant Celoni

F35276150119B

RENOLIT ALKORPLAN F 35276 BRIGHT

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Iberica SA

Carretera del Montnegre s/n

08470 Sant Celoni - Spain

-

System 2+

BS EN 13956 : 2012

BBA N° 0836

-

Proof

E

Pass

MLV >= 1100 N/50 mm

MLV >= 16 %

NPD

MLV >= 20 kg

MLV >= 700 mm

MLV >= 2000 mm

MLV >= 225 N

MLV >= BOJ or 225 N/50 mm

MLV >= BOJ or 1100 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype

18/07/2022



A handwritten signature in blue ink, appearing to be 'Dirk Van der Sype', written over a horizontal line.

UK DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (BS EN 13501-5, BS DD CEN/TS 1187)

Reaction to fire (BS EN 13501-1, BS EN ISO 11925-2)

Watertightness (BS EN 1928/B)

Tensile strength (BS EN 12311-2/A)

Elongation (BS EN 12311-2/A)

Resistance to root penetration (BS EN 13948)

Resistance to static load (BS EN 12730/B and C)

Resistance to impact (BS EN 12691/A)

Resistance to impact (BS EN 12691/B)

Tear resistance (BS EN 12310-2)

Joint peel resistance (BS EN 12316-2)

Joint shear resistance (BS EN 12317-2)

Artificial ageing (BS EN 1297)

Foldability at low temperature (BS EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

Signed for and on behalf of the manufacturer by:

Sant Celoni



F35276180119B

RENOLIT ALKORPLAN F 35276 BRIGHT

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Iberica SA

Carretera del Montnegre s/n

08470 Sant Celoni - Spain

-

System 2+

BS EN 13956 : 2012

BBA N° 0836

-

Froof

E

Pass

MLV >= 1125 N/50 mm

MLV >= 16 %

NPD

MLV >= 20 kg

MLV >= 800 mm

MLV >= 2000 mm

MLV >= 250 N

MLV >= BOJ or 250 N/50 mm

MLV >= BOJ or 1125 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype

18/07/2022

A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype'.

UK DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (BS EN 13501-5, BS DD CEN/TS 1187)

Reaction to fire (BS EN 13501-1, BS EN ISO 11925-2)

Watertightness (BS EN 1928/B)

Tensile strength (BS EN 12311-2/A)

Elongation (BS EN 12311-2/A)

Resistance to root penetration (BS EN 13948)

Resistance to static load (BS EN 12730/B and C)

Resistance to impact (BS EN 12691/A)

Resistance to impact (BS EN 12691/B)

Tear resistance (BS EN 12310-2)

Joint peel resistance (BS EN 12316-2)

Joint shear resistance (BS EN 12317-2)

Artificial ageing (BS EN 1297)

Foldability at low temperature (BS EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

Signed for and on behalf of the manufacturer by:

Sant Celoni



F35276200119B

RENOLIT ALKORPLAN F 35276 BRIGHT

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Iberica SA

Carretera del Montnegre s/n

08470 Sant Celoni - Spain

-

System 2+

BS EN 13956 : 2012

BBA N° 0836

-

Froof

E

Pass

MLV >= 1150 N/50 mm

MLV >= 16 %

NPD

MLV >= 20 kg

MLV >= 1000 mm

MLV >= 2000 mm

MLV >= 275 N

MLV >= BOJ or 275 N/50 mm

MLV >= BOJ or 1150 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype

18/07/2022

A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', written over a horizontal line.