

# TECHNICAL DATA SHEET

## RENOLIT ALKORCLEAN 81026

### Cleaning / Degreasing Agent



## RENOLIT ALKORCLEAN Cleaning / Degreasing Agent - Type 81026

### Application:

The RENOLIT ALKORCLEAN is a Cleaning or Degreasing agent used to clean the flotation line on swimming pool liners and reinforced membranes.

### Technical Data:

- Base: 2-Propanol.
- Color: Colorless
- Viscosity: Approx. 2,08 mPa·s
- Specific Density: 0,89 +/- 0,01 g/cm<sup>3</sup>
- Flash Point: 12°C < 21°C (Highly flammable liquid and vapors.)
- Toxicity: Causes serious eye irritation. May cause drowsiness or dizziness.

### Description:

The RENOLIT ALKORCLEAN eliminates the accumulated dirt on the walls of the pool, along the waterline. Due to its composition, this product is especially effective against oils and fats. No moisture residues on surfaces.

### Placement:

Wet a cleaning cloth (non-abrasive) with the concentrated product and wipe off the stained surface at the floatation line. It may be necessary to decrease the water level to apply the product more comfortably. It is not necessary to empty the pool.

### Packaging:

One litter bottles. Six bottles carton.

### Caution:

As it is flammable product, it must be kept well away from fire, flames and sparks during its storage and usage; also, it should only be used in well-ventilated areas. Do not smoke during its application. Keep container tightly closed. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Storage:

Store in a well-ventilated place.

### For more information:

Read **MSDS**.

